



Eldridge Products, Inc.

Manufacturer of Master-Touch™ Thermal Gas Mass Flowmeters

Eldridge Products, Inc. has pursued innovation and excellence in thermal dispersion gas mass flow measurement for 25 years. With all of the major industry approvals and a variety of configuration and installation choices, our Master-Touch™ flowmeters could be solving your measurement challenges, too.

Master-Touch™ Series 9100MP Flowmeters

MP Series flowmeters are approved for use in hazardous locations (see specifications)

Inline style thermal mass flowmeters include a flow section that is usually specified to match the user's flow conduit and is then plumbed directly into the process line. This design has the sensing elements mounted directly on the flow section for exposure to the process gas. Our inline style flow averaging thermal mass flowmeters are available in sizes from 2" pipe through 4" pipe and are provided with flanged end configurations, as required. Pipe sizes in excess of 4" typically require insertion style thermal mass flow meters.

Remote style thermal mass flowmeters utilize two enclosures. One enclosure is mounted at the point of measurement on the flow section or on the probe assembly. This enclosure may be rated for either hazardous environments or for ordinary, non-hazardous environments, as necessary. The second (remote) enclosure is usually placed in a readily accessible location rated for non-hazardous conditions. (Contact the factory for information concerning remote explosion-proof enclosure). The remote enclosure includes the all of the electrical connections as well as the linearizing electronics and the display/keypad assembly.



Our patented **Flow Averaging Tubes™** (FAT™) use the principle of convective heat transfer to directly measure mass flow, and are well suited to most applications with limited available straight run. In many installations, the up-stream straight run can be reduced to three diameters. The probe has a number of large diameter inlet ports along the length of the upstream impact surface. The pressure at each inlet port is averaged inside the tube to create the axial flow through the tube and across our flow sensor. The gas returns to the main flow stream through the ports located near the sensing elements. Anomalies in the actual flow profile or installations in non-circular ducts may still some require minor adjustment to achieve the best accuracy.



HAUSNET S.R.L.

Tel Argentina: (+54-11) 5219-2211

Tel Chile: (+56-2) 2897-3999

E-Mail: hausnet@hausnet.com.ar

Web: www.hausnet.com.ar

THERMAL GAS MASS FLOW MEASUREMENT APPLICATIONS —

Compressed Air Monitoring

Natural Gas Consumption

Ventilation Hood Alarms

Water & Wastes Aeration

Bio / Digester Gas Production

Landfill Gas Recovery

Boiler Combustion Efficiency

Stack / Flue Gases

Pharmaceutical Clean Rooms

Semiconductor Fabrication

Food Processing

Nitrogen Purging

Pulp & Paper Mills

and many more!



HAUSNET S.R.L.

Tel Argentina: (+54-11) 5219-2211
 Tel Chile: (+56-2) 2897-3999
 E-Mail: hausnet@hausnet.com.ar
 Web: www.hausnet.com.ar

APPROVAL CHOICES

CSA/CUS
 APPROVED INSTRUMENT
 For use in hazardous area locations; Class I Group B, C, D; Class II Group E, F, G; Class III: Encl Type 4X; Class I Zone I; AEx d IIB+H2 IP66; Ex d IIB+H2 IP66; T2 or T3 or T4 as marked; Ta = 0°C to 50°C

ATEX
 APPROVED INSTRUMENT
 For use in hazardous area locations; Ta = 0°C TO 50°C; IP66; Ex d IIB+H2 T4 Gb/ Ex t IIIC T135°C Db or Ex d IIB+H2 T3 Gb/EX t IIIC T200°C Db or Ex d IIB+H2 T2 Gb/EX t IIIC T300°C Db; SIR A 12ATEX1302

IECEx
 APPROVED INSTRUMENT
 For use in hazardous area locations; T2 or T3 or T4 as marked; Ta = 0°C to 50°C; Ex d IIB+H2 T2...T4 Gb IP66; Ex tD A21 IP66 T135°C...T300°C IECEx CSA 11.0014

KOSHA
 APPROVED INSTRUMENT
 For use in hazardous area locations; Class I Group B, C, D; Class II Group E, F, G; Class III; Encl Type 4X; Class I Zone I; AEx d IIB+H2 IP66; Ex d IIB+H2 T2...T4 Gb IP66; Ex tD A21 IP66 T135°C...T300°C

Specifications


Linear signal output	0-5 VDC & 4-20 mA
Signal Interface.....	RS232 & RS485 Modbus RTU embedded HART, Profibus DP (optional)
Accuracy, including linearity (Ref.: 21°C)*	±[1% of Reading + (.5% + .05%/°C of Full Scale)]
Repeatability	±0.2% of Full Scale
Sensor response time.....	1 second
Turn down ratio.....	100:1 (1500 SFPM/7.6 NMPS minimum)
Electronics temperature range.....	-40°-85°C (-40°-185°F)
Gas temperature range	-40°-65°C (-40°-150°F)
Gas pressure effect.....	Negligible over ± 20% of absolute calibration pressure
Pressure rating maximum	500 PSI Std., > 500 PSI special
Input power requirement.....	24VDC @ 250mA 115 VAC 50/60 Hz optional 230 VAC 50/60 Hz optional
Flow Transmitter power requirements	5 watts maximum
RAM Back-up	Lithium Battery
Wetted materials	316 Stainless Steel (Hastelloy optional)
Standard temperature & pressure (STP)	70°F & 29.92" Hg (Air .075 lb./cubic foot)
NIST traceable calibration	Standard

* The accuracy specification applies to the instrument only. EPI is not responsible for measurement errors due to flow profile irregularities caused by installation piping configurations, corrosion on inner pipe surfaces, valve placement, etc.

Approval Choices

- MP Series Flow Transmitter — CSA/CUS, ATEX, IECEx, KOSHA (customer to specify)
- MP Series Remote Enclosure — Ordinary (Non-Hazardous) area locations (standard)
CSA/CUS, ATEX, IECEx, KOSHA (optional; customer to specify)

Remote Electronics Enclosure




Model Number	OD	Length
9116MP	2"	14"
9120MP	2 1/2"	14"
9124MP	3"	14"
9132MP	4"	14"

Not available for Oxygen service.

Four- or six-wire*, twisted pair interconnect cable required between Remote Electronics and Flow Transmitter. Length to be specified
 * Six-wire for Temperature Output

Flow Transmitter Assembly



Eldridge Products, Inc. • 2700 Garden Road • Monterey, CA 93940 USA
 T: 1.831.648.7777 • F: 1.831.648.7780 • E: sales@epiflow.com • www.epiflow.com